

Krilna vrata

Vodič za odabir



ACE TI

Varijanta izdužene ruke

— krilo max 2,00 mt — 24V, 230V, 115V —————> **ACE 3 TI**

— krilo max 3,00 mt — 24V, 230V, 115V —————> **ACE 4 TI**



ACE TA

Varijanta fiksne ruke s krajnjim prekidačima

— krilo max 2,50 mt — 24V, 230V, 115V —————> **ACE 4 TA**

— s mehaničkim krajnjim prekidačima —————> **ACE 4 TA FM**



LEADER TI

Varijanta izdužene ruke

— krilo max 2,00 mt — 115V, 230V —————> **LEADER 3 TI**

— 24V —————> **LEADER 3 24 TI**

— krilo max 2,50 mt — 24V —————> **LEADER 4 24 TI**

— krilo max 2,75 mt — 115V, 230V —————> **LEADER 4 TI**

— krilo max 3,00 mt — 24V —————> **LEADER 5 24 TI**

— krilo max 3,50 mt — 115V, 230V —————> **LEADER 5 TI**



LEADER TA

Varijanta fiksne ruke s krajnjim prekidačima

— krilo max 2,00 mt — 24V —————> **LEADER 4 24 TA**

— krilo max 2,75 mt — 115V, 230V —————> **LEADER 4 TA**

— s mehaničkim krajnjim prekidačima —————> **LEADER 4 TA FM**



ADVANTAGE

Motor s artikuliranom rukom



SHARK

Podzemni motor



WHEELER

"Kolač-pogon"
elektromehanički sustav

